



WOXOL 0W12 API/SP

FULLY SYNTHETIC MOTOR OIL

WOXOL 0W12 fully synthetic engine oil specially designed for Hybrid Electric Vehicles (H.E.V) and Plug-in Hybrid Electric Vehicles (P.H.E.V) equipped with new generation gasoline engines, turbocharged or naturally aspirated, direct or indirect injection, designed to use SAE 0W-8 oil with very low friction and very low HTHS. Suitable also for battery electric vehicles (B.E.V) equipped with thermal gasoline engine used as Range Extender. Suitable for modern gasoline engines requiring a viscosity grade SAE 0W-8 lubricant or a "Fuel Economy" lubricant in viscosity grade 8. Compatible with catalytic converters.

Place Of Use

This ultra-low viscosity engine oil has been specifically developed to meet the challenging requirements of JASO GLV-1 for Japanese car OEM's recommending SAE 0W-12. Designed for turbocharger protection in TGDI engines and has proven performance in hybrid applications.

Features

Total engine protection: enhanced LSPI protection
Fuel economy: superior fuel economy and CO2 reduction
Cold start: excellent fluidity at low temperature.

TEST	METHOD	TYPICAL VALUES
Kinematic Viscosity (100°C) [mm ² /s = cSt]	ASTM D445	6,2
Viscosity Index	ASTM D2270	Min. 149
Flash Point, °C	ASTM D92	Min. 228
Pour Point, °C	ASTM D97	Max. - 45

Approval and Specifications:

API SP, SAE J300

INFILUBE MADENİ YAĞ SANAYİ VE TİCARET A.Ş.

Telefon: +90 216 612 10 22

E-Posta: info@woxollubricants.com / woxollubricants.com

Adres: Cevizli Mah. Zuhâl Cad, 46 E Ritim İstanbul, A5 Blok Daire:25,

Maltepe 34846 İstanbul / Türkiye

INFILUBE[®]
MOTOR OIL AND LUBRICANTS