



## WOXOL 15W40 SN/CF

**FULLY SYNTHETIC MOTOR OIL**

It is a high-performance engine oil developed to provide superior protection and lubrication performance in the engine, produced by blending mineral base oils and special additives, and used in variable operating conditions.

### Place Of Use

For all types of passenger and light commercial vehicle engines, gasoline, diesel and LPG.

### Features

- \*Complete protection against rust and wear in the engine.
- \* High-performance wear control with minimum sludge deposits, provides fluidity over a wide temperature range.
- \* Formulated for all types of passenger and light commercial vehicle engines, gasoline, diesel and LPG, naturally aspirated or turbocharged.

TEST	METHOD	TYPICAL VALUES
Kinematic Viscosity (100°C) [mm <sup>2</sup> /s = cSt]	ASTM D445	12,5 – 16,3
Viscosity Index	ASTM D2270	Min.153
Flash Point, °C	ASTM D92	Min. 212
Pour Point, °C	ASTM D97	Max. - 34

### Approval and Specifications:

API SN/CF, ACEA A3/B4, MB 229.1, VW 501 01/505 00

INFILUBE MADENİ YAĞ SANAYİ VE TİCARET A.Ş.

Telefon: +90 216 612 10 22

E-Posta: info@woxollubricants.com / woxollubricants.com

Adres: Cevizli Mah. Zuhâl Cad, 46 E Ritim İstanbul, A5 Blok Daire:25,

Maltepe 34846 İstanbul / Türkiye

**INFILUBE**<sup>®</sup>  
MOTOR OIL AND LUBRICANTS