



WOXOL 5W30 SP

FULLY SYNTHETIC MOTOR OIL

WOXOL 5W30 SP ILSAC GF-6 is a fully 100% synthetic low viscosity 100% synthetic blended low viscosity oil engineered to perform and are designed to provide the highest levels of engine protection available.

Place Of Use

The product formula has been modified in response to the higher requirements of the latest generation gasoline engines and to meet the API SP category and ILSAC GF-6 quality standart.

Features

- It is recommended for use in all vehicles requiring the use of SAE 5W-30 viscoisty grade engine oils under all driving conditions.
- It provides fuel economy thanks to its low viscosity feature and improved viscosity stability. Thanks to its superior thermal and oxidation stability, it maintains its performance during the longest oil change interval recommended by the vehicle manufacturers.
- Provides excellent protection against engine corrosion and wear.
- Provides excellent protection against wear during start-up of the engine even at the lowest ambient temperatures thanks to its improved viscosity stability.

TEST	METHOT	TYPICAL VALUES
Kinematic Viscosity (100°C) [mm ² /s = cSt]	ASTM D445	9,3 – 12,5
Viscosity Index	ASTM D2270	166
Flash Point, °C	ASTM D92	Min. 225
Pour Point, °C	ASTM D97	Max. - 40

Approval and Specifications:

API SP, ILSAC GF-6, DEXOS 2, GM 6094M, CHRYSLER MS-6395M.

INFILUBE MADENİ YAĞ SANAYİ VE TİCARET A.Ş.

Telefon: +90 216 612 10 22

E-Posta: info@woxollubricants.com / woxollubricants.com

Adres: Cevizli Mah. Zuhâl Cad, 46 E Ritim İstanbul, A5 Blok Daire:25,

Maltepe 34846 İstanbul / Türkiye

INFILUBE[®]
MOTOR OIL AND LUBRICANTS