



WOXOL 5W40 SP/C3

FULLY SYNTHETIC MOTOR OIL

WOXOL 5W40 C3 is a very high performance, fully synthetic MID SAPS lubricant for gasoline and diesel engines, including the ones complying with ACEA C3 standard. WOXOL 5W40 is formulated to reduce pollutant emissions, such as HC, NOx, CO and particles and to protect and ensure longevity of post treatment anti pollution systems, such as particulate filters (GPF, DPF) and three-way catalysts. Oscar Jade Optimum also helps to lengthen the engine life thanks to its excellent resistance to temperature variations and permits an extra-long oil change interval.

Place Of Use

This product meets or exceeds the requirements of the latest API and ACEA industry specifications for petrol and diesel engine oils, as well as the requirements of many major American, and European engine manufacturers. Suitable for use in both gasoline and diesel passenger cars and light commercial vehicles.

Features

- Protects engines from wear and deposit build-up
- LSPI protection
- Fuel Economy
- GPF, DPF protection

TEST	METHOD	TYPICAL VALUES
Kinematic Viscosity (100°C) [mm ² /s = cSt]	ASTM D445	Min.13,5
Viscosity Index	ASTM D2270	Min.165
Flash Point, °C	ASTM D92	Min. 230
Pour Point, °C	ASTM D97	Max. -39

Approval and Specifications:

ACEA C3, A3/B4; API SP; API SN Plus, API SN; MB 229.31/229.51; BMW LL04; dexos 2; Porsche A40; Renault RN0700; Renault RN0710; VW 502.00/505.00, 505.1; Fiat 9.55535-S2; Ford WSS-M2C917-A; PSA B71 2296

E-Posta: info@woxollubricants.com / woxollubricants.com

Adres: Cevizli Mah. Zuhâl Cad, 46 E Ritim İstanbul, A5 Blok Daire:25,
Maltepe 34846 İstanbul / Türkiye