



WOXOL BORON OIL

FULLY SYNTHETIC MOTOR OIL

It is a multi-purpose metal processing liquid used by mixing 5-10% with water in the processing of various metals and alloys formulated with well-refined base oils and strong emulsifiers.

Features

- Prevents the formation of bacteria and prolongs the service life.
- Extends the life of cutting tools and reduces the amount of scrap.
- Protects the system against rust and corrosion thanks to the additives it contains.
- Maintains its performance even in hard waters with the stable emulsion it creates.
- Does not cause smoke and odor.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored tightly closed, under a canopy or in a closed area. Storage temperature should be between (+5)- (+40)°C.

Health and Safety Information

Based on current information, this product is not expected to have any adverse effects on human health when used in its intended location and under the specified conditions of use. Used product should not be burned, poured into soil or wastewater channels. Waste oils should be disposed of by licensed facilities with the characteristics defined in the Waste Oil Control Regulation, by separating them into categories as defined in this regulation. Please read the Material Safety Data Sheet when necessary.

Technical Specifications

TEST	METHOD	TYPICAL VALUES
Density, @15 °C (G / Cm3)	ASTM 1298	0.87- 0.9
pH 3%	DIN 51369	8.0 – 9.8
Refractometer factor		1,5
Corrosion 3%	DIN 51360/2	0/0 Pass
Flashing Point °C	ASTM D 92	Min. 240
Emulsion Appearance		Milk White

INFILUBE MADENİ YAĞ SANAYİ VE TİCARET A.Ş.

Telefon: +90 216 612 10 22

E-Posta: info@woxollubricants.com / woxollubricants.com

Adres: Cevizli Mah. Zuhâl Cad, 46 E Ritim İstanbul, A5 Blok Daire:25,

Maltepe 34846 İstanbul / Türkiye

INFILUBE[®]
MOTOR OIL AND LUBRICANTS